


Products > IP20 Batten > IP20 Batten 1001.1015



IP20 Batten 1001.1015

Line Drawing



Downloads



Physical Specification

Code	1001.1015.01	1001.1015.02	1001.1015.03	1001.1015.04
Product Dimensions (mm)	L600xW75xH26mm	L1200xW75xH26mm	L1500xW75xH26mm	L1800xW75xH26mm
Finish/Color	White	White	White	White
Material	Aluminium+PC	Aluminium+PC	Aluminium+PC	Aluminium+PC
On/Off Switch	N	N	N	N
Cable Length (m)	50cm	100cm	100cm	100cm
Cable Spec.	2x0.75mm ²	2x0.75mm ²	2x0.75mm ²	2x0.75mm ²
Plug	N	N	N	N
Terminal Block	N	N	N	N
Accessories	SS brackets,screw,expansion bolts	SS brackets,screw,expansion bolts	SS brackets,screw,expansion bolts	SS brackets,screw,expansion bolts
Installation	Surface mounted	Surface mounted	Surface mounted	Surface mounted
Class	2	2	2	2

Electrical Characteristics

Code	1001.1015.01	1001.1015.02	1001.1015.03	1001.1015.04
Total Power Consumption Wattage/On-Mode Power	20	40	50	60
Product Voltage	220-240	220-240	220-240	220-240
Hertz	50/60	50/60	50/60	50/60
IP Rating	IP20	IP20	IP20	IP20
Luminous Flux	2400	1800	6000	7200
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A	N/A
SDCM	< 6	< 6	< 6	< 6
CRI	> 80	> 80	> 80	> 80
Power Factor	>0.5	>0.9	>0.9	>0.9
UGR	>19	>19	>19	>19

Function

Code	1001.1015.01	1001.1015.02	1001.1015.03	1001.1015.04
Linkable	N/A	N/A	N/A	N/A
CCT function	N/A	N/A	N/A	N/A
Multi-section Power	N/A	N/A	N/A	N/A
Dimmable	N/A	N/A	N/A	N/A
Sensor	N/A	N/A	N/A	N/A
Emergency	N/A	N/A	N/A	N/A
Battery Spec.	N/A	N/A	N/A	N/A



ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683