



Products > IP20 Batten > IP20 Batten 1001.1012



IP20 Batten 1001.1012

Line Drawing



Downloads



Physical Specification

Code	1001.1012.01	1001.1012.02	1001.1012.03	1001.1012.04	1001.1012.05	1001.1012.06	1001.1012.07	1001.1012.08
Product Dimensions (mm)	L618xW61xH70mm	L1228xW61xH70mm	L1528xW61xH70mm	L1794xW61xH70mm	L618xW61xH70mm	L1228xW61xH70mm	L1528xW61xH70mm	L1794xW61xH70mm
Finish/Color	Gloss White	Gloss White	Gloss White	Gloss White	Gloss White	Gloss White	Gloss White	Gloss White
Material	PC+Iron	PC+Iron	PC+Iron	PC+Iron	PC+Iron	PC+Iron	PC+Iron	PC+Iron
On/Off Switch	N	N	N	N	N	N	N	N
Cable Length (m)	N	N	N	N	N	N	N	N
Cable Spec.	N	N	N	N	N	N	N	N
Plug	N	N	N	N	N	N	N	N
Terminal Block	quick fit	quick fit	quick fit	quick fit	quick fit	quick fit	quick fit	quick fit
Accessories	screw,expansion bolts	screw,expansion bolts	screw,expansion bolts	screw,expansion bolts	screw,expansion bolts	screw,expansion bolts	screw,expansion bolts	screw,expansion bolts
Installation	Surface mounted	Surface mounted	Surface mounted	Surface mounted	Surface mounted	Surface mounted	Surface mounted	Surface mounted
Class	1	1	1	1	1	1	1	1

Electrical Characteristics

Code	1001.1012.01	1001.1012.02	1001.1012.03	1001.1012.04	1001.1012.05	1001.1012.06	1001.1012.07	1001.1012.08
Total Power Consumption Wattage/On-Mode Power	10	18	25	30	20	40	50	60
Product Voltage	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Hertz	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
IP Rating	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Luminous Flux	1200	2160	3000	3600	2400	4800	6000	7200
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD	SMD	SMD	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
SDCM	< 6	< 6	< 6	< 6	< 6	< 6	< 6	< 6
CRI	> 80	> 80	> 80	> 80	> 80	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.9	>0.9	>0.5	>0.9	>0.9	>0.9
UGR	>19	>19	>19	>19	>19	>19	>19	>19

Function

Code	1001.1012.01	1001.1012.02	1001.1012.03	1001.1012.04	1001.1012.05	1001.1012.06	1001.1012.07	1001.1012.08
Linkable	Y	Y	Y	Y	Y	Y	Y	Y
CCT function	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Sensor	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Emergency	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683