


Products > IP65 Batten > IP65 Batten 1003.1009



IP65 Batten 1003.1009

Line Drawing



Downloads



Physical Specification

Code	1003.1009.01	1003.1009.02	1003.1009.03	1003.1009.04	1003.1009.05
Product Dimensions (mm)	L600xW79xH68mm	L1200xW79xH68mm	L1500xW79xH68mm	L1800xW79xH68mm	L600xW79xH68mm
Finish/Color	Grey+Opal finished	Grey+Opal finished	Grey+Opal finished	Grey+Opal finished	Grey+Opal finished
Material	PC+Iron	PC+Iron	PC+Iron	PC+Iron	PC+Iron
On/Off Switch	N	N	N	N	N
Cable Length (m)	N	N	N	N	N
Cable Spec.	N	N	N	N	N
Plug	N	N	N	N	N
Terminal Block	quick fit	quick fit	quick fit	quick fit	quick fit
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted	Surface mounted	Surface mounted
Class	1	1	1	1	1

Electrical Characteristics

Code	1003.1009.01	1003.1009.02	1003.1009.03	1003.1009.04	1003.1009.05
Total Power Consumption Wattage/On-Mode Power	15	19	24	35	24
Product Voltage	220-240	220-240	220-240	220-240	220-240
Hertz	50/60	50/60	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65	IP65	IP65
Luminous Flux	2100	2660	3360	4900	3360
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A	N/A	N/A
SDCM	< 6	< 6	< 6	< 6	< 6
CRI	> 80	> 80	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.5	>0.9	>0.5
UGR	>19	>19	>19	>19	>19

Function

Code	1003.1009.01	1003.1009.02	1003.1009.03	1003.1009.04	1003.1009.05
Linkable	Y	Y	Y	Y	Y
CCT function	Optional	Optional	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional	Optional	Optional
Sensor	Optional	Optional	Optional	Optional	Optional
Emergency	Optional	Optional	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A	N/A	N/A



ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683