

Products > IP65 Batten > IP65 Batten 1003.1008



IP65 Batten 1003.1008

Line Drawing



Downloads



Physical Specification

Code	1003.1008.01	1003.1008.02	1003.1008.03
Product Dimensions (mm)	L625xW42xH32mm	L1150xW42xH32mm	L1450xW42xH32mm
Finish/Color	Opal +Gloss White	Opal +Gloss White	Opal +Gloss White
Material	PC	PC	PC
On/Off Switch	N	N	N
Cable Length (m)	N	N	N
Cable Spec.	N	N	N
Plug	N	N	N
Terminal Block	2-way Terminal Block	2-way Terminal Block	2-way Terminal Block
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted
Class	2	2	2

Electrical Characteristics

Code	1003.1008.01	1003.1008.02	1003.1008.03
Total Power Consumption Wattage/On-Mode Power	18	22	25
Product Voltage	220-240	220-240	220-240
Hertz	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65
Luminous Flux	2050	2550	2880
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A
SDCM	< 6	< 6	< 6
CRI	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.9
UGR	>19	>19	>19

Function

Code	1003.1008.01	1003.1008.02	1003.1008.03
Linkable	N	N	N
CCT function	N	N	N
Multi-section Power	N	N	N
Dimmable	N	N	N
Sensor	N	N	N
Emergency	N	N	N
Battery Spec.	N/A	N/A	N/A

ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683