


Products > IP65 Batten > IP65 Batten 1003.1002



IP65 Batten 1003.1002

Line Drawing



Downloads



Physical Specification

Code	1003.1002.01	1003.1002.02	1003.1002.03
Product Dimensions (mm)	L684xW100xH57mm	L1290xW100xH57mm	L1590xW100xH57mm
Finish/Color	Grey	Grey	Grey
Material	PC	PC	PC
On/Off Switch	N	N	N
Cable Length (m)	N	N	N
Cable Spec.	N	N	N
Plug	N	N	N
Terminal Block	2-way Terminal Block	2-way Terminal Block	2-way Terminal Block
Accessories	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets	screw,expansion bolts,fixing brackets
Installation	Surface mounted	Surface mounted	Surface mounted
Class	2	2	2

Electrical Characteristics

Code	1003.1002.01	1003.1002.02	1003.1002.03
Total Power Consumption Wattage/On-Mode Power	2x9	2x18	2x24
Product Voltage	220-240	220-240	220-240
Hertz	50/60	50/60	50/60
IP Rating	IP65	IP65	IP65
Luminous Flux	1580	3150	4200
Kelvin	3000K/4000K/6500K	3000K/4000K/6500K	3000K/4000K/6500K
LED Package Type			
Lamp/Bulb Specification (if not LED)	T8 LED tube	T8 LED tube	T8 LED tube
Lamp/Bulb included?	N/A	N/A	N/A
SDCM	< 6	< 6	< 6
CRI	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.5
UGR	>19	>19	>19

Function

Code	1003.1002.01	1003.1002.02	1003.1002.03
Linkable	Y	Y	Y
CCT function	N	N	N
Multi-section Power	N	N	N
Dimmable	N	N	N
Sensor	Optional	Optional	Optional
Emergency	N	N	N
Battery Spec.	N/A	N/A	N/A
Others (Solar etc...)	Iron reflector is optional	Iron reflector is optional	Iron reflector is optional



ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683