



Products > Panel / Frame > Panel 1002.1004



Panel 1002.1004

Line Drawing



Downloads



Physical Specification

Code	1002.1004.01	1002.1004.02	1002.1004.03	1002.1004.04	1002.1004.05
Product Dimensions (mm)	L595xW595xH9mm	L1195xW295xH9mm	L1195xW595xH9mm	L595xW295xH9mm	L295xW295xH9mm
Finish/Color	White	White	White	White	White
Material	PC+Aluminium frame	PC+Aluminium frame	PC+Aluminium frame	PC+Aluminium frame	PC+Aluminium frame
On/Off Switch	N	N	N	N	N
Cable Length (m)	0.16	0.16	0.16	0.16	0.16
Cable Spec.	22AWG	22AWG	22AWG	22AWG	22AWG
Plug	N	N	N	N	N
Terminal Block	N	N	N	N	N
Accessories	N	N	N	N	N
Installation	Recessed mounted	Recessed mounted	Recessed mounted	Recessed mounted	Recessed mounted
Class	2	2	2	2	2

Electrical Characteristics

Code	1002.1004.01	1002.1004.02	1002.1004.03	1002.1004.04	1002.1004.05
Total Power Consumption Wattage/On-Mode Power	40	40	60	24	12
Product Voltage	220-240	220-240	220-240	220-240	220-240
Hertz	50/60	50/60	50/60	50/60	50/60
IP Rating	IP20	IP20	IP20	IP20	IP20
Luminous Flux	4000	4000	6000	2400	1200
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A	N/A	N/A
SDCM	< 6	< 6	< 6	< 6	< 6
CRI	> 80	> 80	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.5	>0.5	>0.5
UGR	>19	>19	>19	>19	>19

Function

Code	1002.1004.01	1002.1004.02	1002.1004.03	1002.1004.04	1002.1004.05
Linkable	N/A	N/A	N/A	N/A	N/A
CCT function	Optional	Optional	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional	Optional	Optional
Sensor	Optional	Optional	Optional	Optional	Optional
Emergency	Optional	Optional	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A	N/A	N/A



ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683