


Products > Panel / Frame > Frame 1002.1002



## Frame 1002.1002

### Line Drawing



### Downloads



### Physical Specification

Code	1002.1002.01	1002.1002.02	1002.1002.03
Product Dimensions (mm)	L591×W591×H11mm	L1191×W291×H11mm	L1191×W591×H11mm
Finish/Color	White	White	White
Material	PC+Aluminium frame	PC+Aluminium frame	PC+Aluminium frame
On/Off Switch	N	N	N
Cable Length (m)	0.16	0.16	0.16
Cable Spec.	22AWG	22AWG	22AWG
Plug	N	N	N
Terminal Block	N	N	N
Accessories	N	N	N
Installation	Recessed mounted	Recessed mounted	Recessed mounted
Class	2	2	2

### Electrical Characteristics

Code	1002.1002.01	1002.1002.02	1002.1002.03
Total Power Consumption Wattage/On-Mode Power	40	40	60
Product Voltage	220-240	220-240	220-240
Hertz	50/60	50/60	50/60
IP Rating	IP20	IP20	IP20
Luminous Flux	4000	4000	6000
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A
Lamp/Bulb Included?	N/A	N/A	N/A
SDCM	< 6	< 6	< 6
CRI	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.5
UGR	>19	>19	>19

### Function

Code	1002.1002.01	1002.1002.02	1002.1002.03
Linkable	N/A	N/A	N/A
CCT function	Optional	Optional	Optional
Multi-section Power	Optional	Optional	Optional
Dimmable	Optional	Optional	Optional
Sensor	Optional	Optional	Optional
Emergency	Optional	Optional	Optional
Battery Spec.	N/A	N/A	N/A

## ABOUT US

Introduction  
Research And Development  
Technical Department  
Graphics Department  
Qualification

## PRODUCT

New arrival  
Waterproof  
Bulkhead / Flush  
Ceiling light  
Desk lamp  
Battens  
Panel / Frame  
Downlight  
Counter & Cabinet  
Work light & Flood light

## CONTACT

Email:reon@brightsources.cn  
Phone:+86-574-87309279  
Fax:+86 574 8730 3683