


Products > Downlight > Downlight 1008.1007



Downlight 1008.1007

Line Drawing



Downloads



Physical Specification

| Code | 1008.1007.01 | 1008.1007.02 | 1008.1007.03 | 1008.1007.04 |
|-------------------------|------------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Product Dimensions (mm) | Φ120×H38mm | Φ145×H38mm | Φ170×H38mm | Φ220×H38mm |
| Finish/Color | White | White | White | White |
| Material | PC | PC | PC | PC |
| On/Off Switch | N | N | N | N |
| Cable Length (m) | 12cm | 12cm | 12cm | 12cm |
| Cable Spec. | H03VVH2-F 2×0.75mm ² | H03VV-F 2×0.75mm ² | H03VV-F 2×0.75mm ² | H03VV-F 2×0.75mm ² |
| Plug | N | N | N | N |
| Terminal Block | Junction box | Junction box | Junction box | Junction box |
| Installation | Surface mounted | Surface mounted | Surface mounted | Surface mounted |
| Class | 2 | 2 | 2 | 2 |

Electrical Characteristics

| Code | 1008.1007.01 | 1008.1007.02 | 1008.1007.03 | 1008.1007.04 |
|--|-------------------|-------------------|-------------------|-------------------|
| Total Power Consumption Wattage/On-Mode Power | 9 | 12 | 18 | 24 |
| Product Voltage | 220-240 | 220-240 | 220-240 | 220-240 |
| Hertz | 50/60 | 50/60 | 50/60 | 50/60 |
| IP Rating | IP20 | IP20 | IP20 | IP20 |
| Luminous Flux | 900 | 1200 | 1800 | 2400 |
| Kelvin | 3000K/4000K/6000K | 3000K/4000K/6000K | 3000K/4000K/6000K | 3000K/4000K/6000K |
| LED Package Type | SMD | SMD | SMD | SMD |
| Lamp/Bulb Specification (if not LED) | N/A | N/A | N/A | N/A |
| Lamp/Bulb included? | N/A | N/A | N/A | N/A |
| SDCM | < 6 | < 6 | < 6 | < 6 |
| CRI | > 80 | > 80 | > 80 | > 80 |
| Power Factor | >0.5 | >0.5 | >0.5 | >0.5 |
| UGR | >19 | >19 | >19 | >19 |

Function

| Code | 1008.1007.01 | 1008.1007.02 | 1008.1007.03 | 1008.1007.04 |
|---------------------|--------------|--------------|--------------|--------------|
| Linkable | N | N | N | N |
| CCT function | Optional | Optional | Optional | Optional |
| Multi-section Power | N | N | N | N |
| Dimmable | N | N | N | N |
| Sensor | N | N | N | N |
| Emergency | N | N | N | N |
| Battery Spec. | N/A | N/A | N/A | N/A |

ABOUT US

Introduction
Research And Development
Technical Department
Graphics Department
Qualification

PRODUCT

New arrival
Waterproof
Bulkhead / Flush
Ceiling light
Desk lamp
Battens
Panel / Frame
Downlight
Counter & Cabinet
Work light & Flood light

CONTACT

Email:reon@brightsources.cn
Phone:+86-574-87309279
Fax:+86 574 8730 3683