


Products > Downlight > Downlight 1008.1005



## Downlight 1008.1005

### Line Drawing



### Downloads



### Physical Specification

| Code                    | 1008.1005.01                       | 1008.1005.02                     | 1008.1005.03                     | 1008.1005.04                     | 1008.1005.05                     |
|-------------------------|------------------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|
| Product Dimensions (mm) | Φ95×H26mm                          | Φ120×H26mm                       | Φ145×H26mm                       | Φ170×H26mm                       | Φ220×H26mm                       |
| Finish/Color            | White                              | White                            | White                            | White                            | White                            |
| Material                | PC                                 | PC                               | PC                               | PC                               | PC                               |
| On/Off Switch           | N                                  | N                                | N                                | N                                | N                                |
| Cable Length (m)        | 12cm                               | 12cm                             | 12cm                             | 12cm                             | 12cm                             |
| Cable Spec.             | H03VVH2-F<br>2×0.75mm <sup>2</sup> | H03VV-F<br>2×0.75mm <sup>2</sup> | H03VV-F<br>2×0.75mm <sup>2</sup> | H03VV-F<br>2×0.75mm <sup>2</sup> | H03VV-F<br>2×0.75mm <sup>2</sup> |
| Plug                    | N                                  | N                                | N                                | N                                | N                                |
| Terminal Block          | Junction box                       | Junction box                     | Junction box                     | Junction box                     | Junction box                     |
| Installation            | Recessed                           | Recessed                         | Recessed                         | Recessed                         | Recessed                         |
| Class                   | 2                                  | 2                                | 2                                | 2                                | 2                                |

### Electrical Characteristics

| Code  | 1008.1005.01      | 1008.1005.02      | 1008.1005.03      | 1008.1005.04      | 1008.1005.05      |
|---|-------------------|-------------------|-------------------|-------------------|-------------------|
| Total Power Consumption Wattage/On-Mode Power | 5                 | 9                 | 12                | 18                | 24                |
| Product Voltage                               | 220-240           | 220-240           | 220-240           | 220-240           | 220-240           |
| Hertz   | 50/60             | 50/60             | 50/60             | 50/60             | 50/60             |
| IP Rating                                     | IP20              | IP20              | IP20              | IP20              | IP20              |
| Luminous Flux                                 | 500               | 900               | 1200              | 1800              | 2400              |
| Kelvin  | 3000K/4000K/6000K | 3000K/4000K/6000K | 3000K/4000K/6000K | 3000K/4000K/6000K | 3000K/4000K/6000K |
| LED Package Type                              | SMD               | SMD               | SMD               | SMD               | SMD               |
| Lamp/Bulb Specification (if not LED)          | N/A               | N/A               | N/A               | N/A               | N/A               |
| Lamp/Bulb included?                           | N/A               | N/A               | N/A               | N/A               | N/A               |
| SDCM  | < 6               | < 6               | < 6               | < 6               | < 6               |
| CRI   | > 80              | > 80              | > 80              | > 80              | > 80              |
| Power Factor                                  | >0.5              | >0.5              | >0.5              | >0.5              | >0.5              |
| UGR   | >19               | >19               | >19               | >19               | >19               |

### Function

| Code                | 1008.1005.01 | 1008.1005.02 | 1008.1005.03 | 1008.1005.04 | 1008.1005.05 |
|---------------------|--------------|--------------|--------------|--------------|--------------|
| Linkable            | N            | N            | N            | N            | N            |
| CCT function        | Optional     | Optional     | Optional     | Optional     | Optional     |
| Multi-section Power | N            | N            | N            | N            | N            |
| Dimmable            | N            | N            | N            | N            | N            |
| Sensor              | N            | N            | N            | N            | N            |
| Emergency           | N            | N            | N            | N            | N            |
| Battery Spec.       | N/A          | N/A          | N/A          | N/A          | N/A          |



#### ABOUT US

Introduction  
Research And Development  
Technical Department  
Graphics Department  
Qualification

#### PRODUCT

New arrival  
Waterproof  
Bulkhead / Flush  
Ceiling light  
Desk lamp  
Battens  
Panel / Frame  
Downlight  
Counter & Cabinet  
Work light & Flood light

#### CONTACT

Email: [reon@brightsources.cn](mailto:reon@brightsources.cn)  
Phone: +86-574-87309279  
Fax: +86 574 8730 3683