


Products > Downlight > Downlight 1008.1002



## Downlight 1008.1002

### Line Drawing



### Downloads



### Physical Specification

Code	1008.1002.01	1008.1002.02	1008.1002.03	1008.1002.04	1008.1002.05
Product Dimensions (mm)	Φ95xH26mm	Φ120xH26mm	Φ145xH26mm	Φ170xH26mm	Φ220xH26mm
Finish/Color	White	White	White	White	White
Material	PC	PC	PC	PC	PC
On/Off Switch	N	N	N	N	N
Cable Length (m)	12cm	12cm	12cm	12cm	12cm
Cable Spec.	H03VVH2-F 2x0.75mm <sup>2</sup>	H03VV-F 2x0.75mm <sup>2</sup>	H03VV-F 2x0.75mm <sup>2</sup>	H03VV-F 2x0.75mm <sup>2</sup>	H03VV-F 2x0.75mm <sup>2</sup>
Plug	N	N	N	N	N
Terminal Block	N	N	N	N	N
Installation	Recessed	Recessed	Recessed	Recessed	Recessed
Class	2	2	2	2	2

### Electrical Characteristics

Code	1008.1002.01	1008.1002.02	1008.1002.03	1008.1002.04	1008.1002.05
Total Power Consumption Wattage/On-Mode Power	5	9	12	18	24
Product Voltage	220-240	220-240	220-240	220-240	220-240
Hertz	50/60	50/60	50/60	50/60	50/60
IP Rating	IP20 / IP54	IP20 / IP54	IP20 / IP54	IP20 / IP54	IP20 / IP54
Luminous Flux	500	900	1200	1800	2400
Kelvin	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
LED Package Type	SMD	SMD	SMD	SMD	SMD
Lamp/Bulb Specification (if not LED)	N/A	N/A	N/A	N/A	N/A
Lamp/Bulb included?	N/A	N/A	N/A	N/A	N/A
SDCM	< 6	< 6	< 6	< 6	< 6
CRI	> 80	> 80	> 80	> 80	> 80
Power Factor	>0.5	>0.5	>0.5	>0.5	>0.5
UGR	>19	>19	>19	>19	>19

### Function

Code	1008.1002.01	1008.1002.02	1008.1002.03	1008.1002.04	1008.1002.05
Linkable	N	N	N	N	N
CCT function	Optional	Optional	Optional	Optional	Optional
Multi-section Power	N	N	N	N	N
Dimmable	N	N	N	N	N
Sensor	N	N	N	N	N
Emergency	N	N	N	N	N
Battery Spec.	N/A	N/A	N/A	N/A	N/A



#### ABOUT US

Introduction  
Research And Development  
Technical Department  
Graphics Department  
Qualification

#### PRODUCT

New arrival  
Waterproof  
Bulkhead / Flush  
Ceiling light  
Desk lamp  
Battens  
Panel / Frame  
Downlight  
Counter & Cabinet  
Work light & Flood light

#### CONTACT

Email: [reon@brightsources.cn](mailto:reon@brightsources.cn)  
Phone: +86-574-87309279  
Fax: +86 574 8730 3683